

TO SEPARATE, HOLD TOP AND BOTTOM EDGES, SNAP-APART AND DISCARD CARBON

| FORM PTO-892 (REV. 2-92) | | U.S. DEPARTMENT OF COMMERCE PATENT AND TRADEMARK OFFICE | | SERIAL NO. | GROUP PART UNIT | ATTACHMENT TO PAPER NUMBER | 6 | | |
|---|--|---|------|--------------|-----------------|-------------------------------------|----------------------------|----------------------------|--------------|
| | | NOTICE OF REFERENCES CITED | | APPLICANT(S) | FORBES | | | | |
| U.S. PATENT DOCUMENTS | | | | | | | | | |
| * | | DOCUMENT NO. | DATE | NAME | CLASS | SUB-CLASS | FILING DATE IF APPROPRIATE | | |
| A | | 5 285 088 | 2/94 | Sato et al. | 257 | 616 | — | | |
| B | | 5512772 | 4/96 | Maeda et al. | 257 | 616 | 6/91 | | |
| C | | | | | | | | | |
| D | | | | | | | | | |
| E | | | | | | | | | |
| F | | | | | | | | | |
| G | | | | | | | | | |
| H | | | | | | | | | |
| I | | | | | | | | | |
| J | | | | | | | | | |
| K | | | | | | | | | |
| FOREIGN PATENT DOCUMENTS | | | | | | | | | |
| * | | DOCUMENT NO. | DATE | COUNTRY | NAME | CLASS | SUB-CLASS | PERTINENT SHTS. DWG. | PP. SPEC. |
| L | | | | | | | | | |
| M | | | | | | | | | |
| N | | | | | | | | | |
| O | | | | | | | | | |
| P | | | | | | | | | |
| Q | | | | | | | | | |
| OTHER REFERENCES (Including Author, Title, Date, Pertinent Pages, Etc.) | | | | | | | | | |
| R | | IEEE Electron Device Letters, Vol. 12, No. 4, pg 154-156, April 1991 by Nayak et al. | | | | | | | |
| S | | | | | | | | | |
| T | | | | | | | | | |
| U | | | | | | | | | |
| EXAMINER | | DATE | | | | | | | |
| A copy of this reference is not being furnished with this office action. (See Manual of Patent Examining Procedure, section 707.05 (a).) | | | | | | | | | |